

# UNIT 11

## TECH SHEET



DB Video \* Kontichsesteenweg 39 \* 2630 Aartselaar \* België  
+32 3 843 25 85 \* [info@dbvideo.tv](mailto:info@dbvideo.tv) \* [www.dbvideo.tv](http://www.dbvideo.tv)





## UNIT11 SPECIFICATIONS

### Truck: Daf CF

Engine 370 HP Euro 6 with Silent modus  
Length 11,15 m  
Width Expanded 4,2 m  
Required free workspace: 12,5m x 5m

### Production

4K – HDR compatible IP Ready  
8 Camera slots Grassvalley and Sony Compatible both provided with fiber and triax cabled.  
2 Util slots for wireless cam or highspeed camera.  
Kahuna 6400, 3 ME with 48 3G/HD SDI or 12 4K inputs, 24 3Gb/HD SDI outputs or 6 4K Outputs including format fusion 3 on all inputs, 16 format fusion outputs.  
Modular Maverick 3-ME Panel operation panel for Kahuna 6400.  
Riedel Mediornet Decentralized video matrix solution based on MicroN and MetroN frames (204 x 204 in-outs).  
24 Riedel Multiviewer outputs possible with a total of 108 PIPS possible.  
Sony OLED Monitorwall

### Record & playback

Two EVS Slots 6RU each with 16 HD/SDI inputs or 4 4K inputs with 10 Gig lan connection.  
6 flexible slots for GFX, Recordings PC's, or any equipment needed today in the broadcast field.  
24-ports - 10 Gbit mediaswitch compatible with RJ 45 and SFP/ AOC.

### Tech area

Two Sony OLED vision positions with leader multi sdi waveform monitor  
One flexible 4K Sony BVM X-300 with Leader monitor for 4K HDR productions  
Lawo VSM control software with backup server.  
Riedel MediorNet multimedia network for stagebox or remote hub.

### Sound

Lawo MC2 56 with 32 faders  
Lawo Nova Compact router with 16 MADI ports and 192 channels of DSP  
External Lawo DALLIS stageboxes with fibre cabling  
Genelec 5.1 Digital SAM monitors  
64 channel multitrack recording  
Lexicon PCM 96 Surround fx preprocessor  
Riedel Artist 64 frame with MADI connection, 1100 series panels  
Riedel connect Trio and Glennsound GSM Hybrid for external communication  
Riedel RiFace and Motorola radios DP series for wireless communication  
AEQ Phoenix STRATOS Dual channel audiocodec with IP, ISDN

